



Description: _____

Housing available in either Aluminum or Stainless Steel.
 Valves, Key 2 and Key 3, Normally Closed, Pilot to Open
 Valve, Key 4 is Normally Open, Pilot to Close. and fits in a smaller cavity.
 Valves 2 and 3 fit Cavity C-8542, Maximum Valve Diameter 1.50"
 Valve 4 fits Cavity C-8502
 Valves Have 1/8 NPT Pilot Port and are 40:1 Pilot Ratio.

Port Designations: _____

- 1 to Outlet
- 2 to Inlet
- 3 to Inlet
- 4 to Return to Tank or Vent

Operation: _____

- Pilot Open Key 2 Valve to connect Port 2 to Port 1
- Pilot Open Key 3 Valve to connect Port 3 to Port 1
- Pilot Closed Key 4 Valve to enable pressurization of Port 1
- Un-Pilot (de-Energize) Key 4 Valve to Return to Tank or Vent Port 1
- Loss of Pilot Pressure Condition:
 Valves 2 & 3 Closed
 Valve 4 Open to Tank or Vent Port 1

Housing Catalog Numbers:

Valves ordered separately.

Aluminum Housing

3000 PSIG Rated

CAT. NO. PORTING

S2955-1 1/8 NPT

S2955-2 1/4 NPT

S2955-3 3/8 NPT

S2955-4 SAE4

S2955-6 SAE6

STAINLESS HOUSING

5000 PSIG Rated

CAT. NO. PORTING

S2955-3S 1/8 NPT

S2955-2S 1/4 NPT

S2955-3S 3/8 NPT

S2955-4S SAE4

S2955-6S SAE6

S2955 Series Housings