


6343 RIVER ROAD SE ■ CLEAR LAKE, MN 55319 USA
 Telephone: 320-743-2276 ■ Fax: 320-743-3723
 mailbox@doering.com ■ www.doering.com



Select DOERING Solenoid Option (*)	Order		Ref. MAC P/N Solenoid Only	Electrical Information	Condition of (P) N/C or N/O	Connect MAC ports
	DOERING P/N Assembled	OR DOERING P/N Open Items (Kit)				
A	1202090A	1202090AB	35A-AAA-DAAA-1BA	110/120VAC 50/60Hz 5.4 Watts	Normally Closed	1 - (P) Air Inlet 2 - (C) Doering Pilot 3 - (E) Exhaust
B	1202090B					1 - (E) Exhaust 2 - (C) Doering Pilot 3 - (P) Air Inlet
C	1202090C	1202090CD	35A-AAA-DACA-1BA	24VAC 50Hz, 7.4W 60Hz, 5.7W	Normally Closed	1 - (P) Air Inlet 2 - (C) Doering Pilot 3 - (E) Exhaust
D	1202090D					1 - (E) Exhaust 2 - (C) Doering Pilot 3 - (P) Air Inlet
G	1202090G	1202090GH	35A-AAA-DDAA-1BA	24VDC 5.4 Watts	Normally Closed	1 - (P) Air Inlet 2 - (C) Doering Pilot 3 - (E) Exhaust
H	1202090H					1 - (E) Exhaust 2 - (C) Doering Pilot 3 - (P) Air Inlet
J	1202090J	1202090JK	35A-AAA-DDBA-1BA	12VDC 5.4 Watts	Normally Closed	1 - (P) Air Inlet 2 - (C) Doering Pilot 3 - (E) Exhaust
K	1202090K					1 - (E) Exhaust 2 - (C) Doering Pilot 3 - (P) Air Inlet

Assembly 1202090* Solenoid Pilot Options

* = Select Voltage and Condition

Exhaust Muffler 1200836 - Assemble without sealant.

1/8" NPT Brass Short Nipple 1202091 - Assemble with sealant.

This series of Solenoid Pilot Valves has 18" Flying Leads.

Solenoid Options & Assembly Guide using MAC brand valves.

PSI Limit is 120 PSI for illustrated MAC valves (P) Air Inlet.

1202090 Series

Solenoid Pilot Options