

1200912M30

Primary Vendor/Manufacturer: Associated Spring (DR: 7064)

Associated Spring Part Number: C1100-085-0875-S (302 SST.)

Spring Material: 302 SST. Stress relieved and Passivated (per manufacturer, verbal).

Approximate Solid Height: .348"

Spring Rate: 37.57 Lb/in

Recommended Minimum Working Height (L1): .527"

Load Force at .527" = 13.08# Force

Weight Each: Weight Lbs/1000

1200912M33

Primary Vendor/Manufacturer: Associated Spring (DR: 7064)

Associated Spring Part Number: C1100-085-0875-X (316 SST.)

Spring Material: 316 SST. Stress relieved and Passivated (per manufacturer, verbal).

Approximate Solid Height: .348"

Spring Rate: 37.57 Lb/in

Recommended Minimum Working Height (L1): .474"

Load Force at .474" = 15.07# Force

Load Force at .527" = 13.08# Force

Weight Each: Weight Lbs/1000

Receiving Verify:

Actual Record

Receiving Inspector

Date

Manufacturer (ASR) Order# _____

Manufacturer Part Number _____

Material Call out on packing slip _____

Outside Diameter: $\varnothing 1.10 \pm .01$ _____

Wire Diameter: $\varnothing .085 \pm .003$ _____

Free Length: $.875 \pm .01$ _____

Receiving Inspection Document

1200912 REV. 06

1200912M30 1200912M33

Spring

6343 River Rd. SE * Clear Lake, MN 55319
Phone: 320 743-2276 Fax: 743-3723
mailbox@doering.com www.doering.com

DOERING

CO